

DEHUMIDIFIER



- The ceiling of the drying rooms are calculated fully isolated (must be covered at least 4mm high dense styofom including ceiling) with ceiling height of 2.30 meters.
- Channel thpe model (HKS Models) drying machines are mounted outside the drying room.
- Production of Air conditioning channels to be connected to drying machines and inside the room is not wihtin the frame of the responsibility of our company.
- All our equipments work with three phase energy feding.

SPECIFICATIONS	HKS 350	HKS 450	HKS 600
Carpet Drying Capacity	350 m ²	450 m ²	600 m ²
Drying Room Size	70 m ³	100 m ³	150 m ³
Energy Consumption (hour)	5,5 kW	7,5 kW	8 kW
Amper	9 A	10,3 A	14.8 A
Maximum Humidity Removal Capacity	720 lt	800 lt	1120 lt
Operating Temperature Range	+5 -+55	+5 -+55	+5 -+55
Operating Humidity Range	%20 - %100	%20 - %100	%20 - %100
Phase / Voltage / Frequency	380 / 430	380 / 430	380 / 430
Weight	175 kg	185 kg	210 kg



HAYIKAMA

INDUSTRIAL CARPET CLEANING SYSTEMS

 Minarelicavus Mah.
105 (290) Sok. No:8/1 Nilufer/Bursa/TURKEY

 +90 224 411 0 356

 +90 224 411 1 013

 export@hayikama.com

 www.hayikama.com