

ABOUT US

Our company entered the professional business world with hand weaving carpet production in early 70s and included carpet cleaning in its service range upon intense demands from the customers in 80s. Our company has visionary view point that provides identity to our institution. The fact that carpet cleaning costs were not economical in that period made us perform higher quality production in conformity with customer expectations, models with new technology were made.

HAYIKAMA started the production of the first machines in 2000s as a result of knowledge accumulation in the industrial production and carried its quality a step further. New machine models were designed and mass production started in order to increase the effeciency and reduce the cost of carpet cleaning.

HAYIKAMA is a company specialized in the manufacturing of industrial carpet cleaning systems. The company started its activities in 1970 by producing hand-knotted carpets then incorporated carpet washing services to its structure in 1980. The comapny invested in in the techology related the carpet cleaning systems in order to increase the quality production and reduce the carpet washing cost. Since 2005, HAYIKAMA started the manufacturing of new machines and increased the quality and efficiency of its cleaning systems by producing new machine models.

The company is working both domestically and internationally by exporting its machines to more than 48 countries around the world with a backround of 35 years experience. HAYIKAMA produces a full professional line for industrial carpet cleaning that regroups the following machines : Automatic dust remover, Automatic carpet washing machine, Automatic carpet spin dryer HAYIKAMA is also a solution partner and offers consultancy and training to its customers.

Our institution plays an active role in R&D works and is a leader in its sector and succeeded in being the symbol of quality for almost 45 years in gaining the trust of its customers.

OUR VALUES

Hayıkama who provides service in its sector for many years believes in open and transparent communication in allbusiness processes from production to after sales service and the power of empathetic approach in bilateral relations. Rooted past of our company is based on the following principles:

-Customer satisfaction is more important than anything else. We listen to our customers and produce suitable and reasonable solutions suitable for their requirements which provide success and income in professional life.

-We take pains to budgets in raw material purchasing in order to decrease our production costs and offer quality with most economical prices.

-We follow new technologies closely and produce solutions that allow business developments and growths of our customers.

-We believe that environmental awareness should increase for protecting natural resources which diminish gradually. Hayıkamatries to develop technical products that save water and energy.

-As a company open for innovations wepay value to feedbacks from all our stake holders for continuous development. We realize those coinciding with our principles. We thank to all our partners whosupport our development.

-We produce products which touch thefuture with cheery and experienced employees trained well.








SPECIFICATIONS


- Single brushing unit (with 4 or 5 brushes depending on the size)
- High pressure rinsing unit
- Moving scrapper unit
- Rolling unit
- Hot-dipped galvanized chassis with stainless steel covers
- Ability to wash all types of carpets
- Speed control operating system
- Fragmental conveyor belt system that prevents belt stell
- Button control system that provides detergent, electricity and water conservation
- Automatic detergent and water pump system
- Pneumatic brush pressure system
















SINGLE BRUSHING UNIT
HIGH PRESSURE RINSING UNIT
MOVING SCRAPPER UNIT
CYLINDRICAL DOWN ROLL BRUSH
ROLLING SYSTEM

















SPECIFICATIONS	HYM 284-E	HYM 335-E	HYM 435-E	
Max. Carpet Width	260 cm	320 cm	420 cm	
Dimensions	330x225x170 cm 390x225x170 cm		490x225x170 cm	
Weight	1600 kg	2200 kg	2700 kg	
Washing Capacity	150 m²/h 180 m²/h		240 m²/h	
Number of Brushes	4 disc + moving scrapper	5 disc + moving scrapper	5 disc + moving scrapper	
	+ down roll brush	+ down roll brush	+ down roll brush	
Engine Power	9 kW	10 kW	10 kW	
Electricity		3 phase / 380 V / 50 Hz		
Button Control	\checkmark			
Speed Control	\checkmark			
Electronic Sensor System	\checkmark			
Detergent Tank	\checkmark			
Automatic Detergent Pump System	\checkmark			
Carpet Trolley	\checkmark			
Rolling System	\checkmark			










SPECIFICATIONS


- First brushing unit (with 4 or 5 brushes depending on the size)
- Second brushing unit (with 4 or 5 brushes depending on the size)
- High pressure rinsing unit
- Vacuum unit
- Upper combing brush
- Down combing brush
- Rolling unit
- Stainless steel and hot-dipped galvanized chassis
- Ability to wash all types of carpets
- Speed control operating system
- Fragmental conveyor belt system that prevents belt stell
- PLC control system that provides detergent, electricity and water conservation
- Touch screen panel control
- Automatic detergent and water pump system
- Pneumatic brush pressure system
















- FIRST BRUSHING UNIT
- SECOND BRUSHING UNIT
- **4** HIGH PRESSURE RINSING UNIT
- ♦ VACUUM UNIT
- **UPPER COMBING BRUSH**
- OOWN COMBING BRUSH
- **ROLLING SYSTEM**

















SPECIFICATIONS	HYM 288-F	HYM 338-F	HYM 4310-F	
Max. Carpet Width	260 cm 320 cm		420 cm	
Dimensions	380x410x240 cm	430x410x240 cm	530x410x240 cm	
Weight	3000 kg	3500 kg	4600 kg	
Washing Capacity	150 m²/h	180 m²/h	240 m²/h	
Number of Brushes	8 disc + 2 combing brushes	8 disc + 2 combing brushes	10 disc + 2 combing brushes	
Engine Power	16,5 kW	18 kW	20 kW	
Electricity	3 phase / 380 V / 50 Hz			
Touch Control Panel	\checkmark			
Speed Control	\checkmark			
Electronic Sensor System	\checkmark			
Detergent Tank	\checkmark			
Automatic Detergent Pump System	\checkmark			
Carpet Trolley	\checkmark			
Rolling System	\checkmark			










- PNEUMATIC DOOR LOCK SYSTEM
- DELTA STAR WORKING SYSTEM
- TIME ADJUSTMENT WORKING SYSTEM
- O PNEUMATIC BRAKE SYSTEM
- LOCKING SAFETY SENSOR











AUTOMATIC CARPET SPIN DRYER

















SPECIFICATIONS	HSS 265-40	HSS 320-40	HSS 320-47	HSS 420-40	HSS 420-47
Outer Drum	Painted				
Inner Drum	Stainless Steel				
Max. Carpet Width	265 cm	320 cm	320 cm	420 cm	420 cm
Dimensions	110x320x135 cm	110x380x135 cm	120x395x150 cm	120x495x150 cm	120x495x150 cm
Weight	650 kg	800 kg	1200 kg	1350 kg	1500 kg
Diameter of Inner Drum	40 cm	40 cm	47 cm	40 cm	47 cm
Thickness of Inner Drum	3 mm	3 mm	4 mm	4 mm	4 mm
Capacity	270 m²/h	360 m²/h	360 m²/h	480 m²/h	480 m²/h
Engine Power	5,5 kW	7,5 kW	7,5 kW	11 kW	11 kW
Maximum RPM	1300 rpm	1300 rpm	1000 rpm	1000 rpm	1000 rpm
Voltage	3 phase / 380 V / 50 Hz				
Inverter Working System	Optional				
Time Adjustment Working System	\checkmark				
Suspension System	\checkmark				
Pneumatic Door Lock System	\checkmark				
Pneumatic Brake System	\checkmark				
Sensor System	\checkmark				

WATCH MACHINE VIDEO










DOUBLE SHAKER











DUST REMOVER




SPECIFICATIONS	HTM 250 HTM 350		HTM 450	
Chassis		Painted		
Max. Carpet Width	260 cm 320 cm		420 cm	
Dimensions	160x360x130 cm	160x420x130 cm	160x520x130 cm	
Weight	1200 kg	1450 kg	1900 kg	
Capacity	180 m²/h	240 m²/h	300 m²/h	
Motor Power	4,5 kW	4,5 kW	5,2 kW	
Vacuum Power	1800 m³/h	1800 m³/h	3500 m³/h	
Voltage	3 phase / 380 V / 50 Hz			
Rolling Mechanism	\checkmark			
Speed Control	\checkmark			
Control Panel	\checkmark			
Filter	\checkmark			


WATCH MACHINE VIDEO













SWEEPING AND VACUUM MACHINE



SPECIFICATIONS	HPM 250	HPM 350	HPM 450	
Chassis	Painted			
Band width	260 cm	320 cm	420 cm	
Dimensions	310x150x200 cm	370x150x200 cm	470x150x200 cm	
Weight	1350 kg	1500 kg	1750 kg	
Sweeping Capacity	180 m²/h	240 m²/h	300 m²/h	
Number of Brush	1 roll brush	1 roll brush	1 roll brush	
Motor Power	4,5 kW	4,5 kW	6 kW	
Vacuum Power	1800 m ³/h	1800 m ³/h	3500 m ³ /h	
Sub Cleaning Brush	Optional			
Voltage	3 phase / 380 V / 50 Hz			
Control Panel	\checkmark			
Speed control	\checkmark			
Vacuum system	\checkmark			
Manual Rolling	\checkmark			

WATCH MACHINE VIDEO





SPECIFICATIONS

- High Moisture Removal Capacity
- Durable Construction
- High Airflow Capacity
- The drying room should be fully isolated (it must be covered with at least 4 mm high dense styrofoam including the ceiling).
- All our equipments work with three phase energy feding.





DEHUMIDIFIER





SPECIFICATIONS	HKS 350	HKS 450	HKS 600
Carpet Drying Capacity	350 m ²	450 m ²	600 m ²
Drying Room Size	70 m ³	100 m ³	150 m ³
Energy Consumption (hour)	5,5 kW	7,5 kW	8 kW
Amper	9 A	10,3 A	14.8 A
Maximum Humidity Removal Capacity	720 lt	800 lt	1120 lt
Operating Temperature Range	+5 -+55	+5 -+55	+5 -+55
Operating Humidity Range	%20 - %100	%20 - %100	%20 - %100
Phase / Voltage / Frequency	380 / 430	380 / 430	380/430
Weight	175 kg	185 kg	210 kg

OUR WORLDWIDE PRESENCE





MINARELICAVUS MAH. 105.(290)SK. NO:8/1 NILUFER/BURSA/TURKEY +90 224 411 0 356 EXPORT@HAYIKAMA.COM WWW.HAYIKAMA.COM